



american gas & chemical co. ltd.
220 PEGASUS AVE
NORTHVALE, NEW JERSEY 07647
201-767-7300, FAX 201-767-1741

Safety Data Sheet

Issue Date: 01-Feb-2002

Revision Date: 20-Nov-2023

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Fluorofinder III Shotpeen Tracer

Other means of identification

SDS # AGC-015

Product Code FF-IIIAL

UN/ID No UN1193

Other Information Package type: 1 pint HDPE bottle.

Recommended use of the chemical and restrictions on use

Recommended Use Shotpeen Tracer Paint.

Details of the supplier of the safety data sheet

Manufacturer Address AMERICAN GAS & CHEMICAL COMPANY, LTD
220 Pegasus Avenue
Northvale NJ 07647

Emergency Telephone Number

Company Phone Number Phone: 201-767-7300 Fax: 201-767-1741

Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Clear yellow liquid **Physical State** Liquid **Odor** Acetone

Classification

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed

Signal Word

Danger

Hazard Statements

Causes serious eye irritation

May cause drowsiness or dizziness

Highly flammable liquid and vapor



Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Get medical attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician

IN CASE OF FIRE: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Methyl ethyl ketone	78-93-3	98

4. FIRST-AID MEASURES

First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	If eye contact occurs, flush with water for at least 15 minutes and call a physician.
Skin Contact	In case of contact, wash skin thoroughly with soap and water. Remove any contaminated clothing and wash before reuse.
Inhalation	If overcome by vapor, remove from exposure and call physician immediately. If breathing is irregular or has stopped, start resuscitation; administer oxygen, if available.
Ingestion	If ingested, do not induce vomiting. Call a physician immediately.

Most important symptoms and effects

Symptoms	Vapor irritates eyes, nose and throat. Liquid is irritating to skin causing dermatitis. Can cause headache, nausea, vomiting, dizziness, gastrointestinal irritation, and central nervous system depression.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician	MEDICAL CONDITIONS KNOWN TO BE AGGRAVATED BY EXPOSURE TO PRODUCT: Respiratory system disease, skin disorders.
---------------------------	--

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical or alcohol type foam.

Unsuitable Extinguishing Media Water spray may be ineffective.

Specific Hazards Arising from the Chemical

Highly flammable liquid and vapor. Vapors may form explosive mixtures with air.

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool exposed containers with water spray. Avoid breathing vapor or fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Remove all ignition sources. Recover free liquid. Ventilate confined spaces. Wear protective clothing as described in Section 8 of this safety data sheet.
For Emergency Responders	Follow applicable OSHA regulations (29 CFR 1910.120).
Environmental Precautions	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for Clean-Up	Use clean non-sparking tools to collect absorbed material. Sweep up absorbed material and shovel into suitable containers for disposal. Discard any product, residue, disposable container or liner in full compliance with federal, state, and local regulations. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wash face, hands, and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only with adequate ventilation. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep containers closed when not in use. Ground/bond container and receiving equipment. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Use personal protection recommended in Section 8. Keep cool.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers closed when not in use. Do not handle or store near heat, sparks, flame or strong oxidants. Store locked up. Store in cool place (under 75°F).

Incompatible Materials

Strong oxidizing agents, strong bases, caustics, mineral acids and ammonia, halogens, plastics, rubber.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl ethyl ketone 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m ³ (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m ³	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³

Appropriate engineering controls

Engineering Controls

Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the SDS.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Use splash goggles or face shield when contact may occur.

Skin and Body Protection

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact. Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could result in prolonged or repeated skin contact.

Respiratory Protection

Chemical cartridge respirator with organic vapor cartridge is recommended. Above this level, a self-contained breathing apparatus is recommended.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Odor	Acetone
Appearance	Clear yellow liquid	Odor Threshold	Not determined
Color	Clear yellow	Remarks • Method	
Property	Values		
pH	Not available		
Melting Point/Freezing Point	Not determined		
Boiling Point/Boiling Range	79.6°C / 175.28°F		
Flash Point	-6.66°C / 20°F	ASTM D 56	
Evaporation Rate	5.6	(Water = 1) (butyl acetate = 1)	
Flammability (Solid, Gas)	Not determined		
Upper Flammability Limits	11.4%		
Lower Flammability Limit	1.4%		
Vapor Pressure	190 mm Hg	@ 38°C (100°F)	
Vapor Density	2.5	(Air=1)	
Specific Gravity	0.807	@ 20°C (68°F)	
Water Solubility	Appreciable		
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Auto-ignition Temperature	Not determined		
Decomposition Temperature	Not determined		

AGC-015 - Fluorofinder III Shotpeen Tracer
Kinematic Viscosity Not determined
Dynamic Viscosity Not determined
Explosive Properties Not determined
Oxidizing Properties Not determined
Additional Information Percent volatile: 97

Revision Date: 20-Nov-2023

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children.

Incompatible Materials

Strong oxidizing agents, strong bases, caustics, mineral acids and ammonia, halogens, plastics, rubber.

Hazardous Decomposition Products

If burned, CO and/or CO₂.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes serious eye irritation.
Skin Contact May cause temporary irritation on skin contact.
Inhalation Vapor may irritate respiratory tract. May cause drowsiness or dizziness.
Ingestion May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone 78-93-3	= 2737 mg/kg (Rat)	= 6480 mg/kg (Rabbit)	-

Information on physical, chemical and toxicological effects

Symptoms EFFECTS OF OVEREXPOSURE: Vapor irritates eyes, nose and throat. If overcome by vapors, remove to fresh air and if breathing stops, give artificial respiration. Keep individual calm.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

STOT - single exposure May cause drowsiness or dizziness.

Numerical measures of toxicity Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Methyl ethyl ketone 78-93-3		3130 - 3320: 96 h Pimephales promelas mg/L LC50 flow-through	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	520: 48 h Daphnia magna mg/L EC50 5091: 48 h Daphnia magna mg/L EC50 4025 - 6440: 48 h Daphnia magna mg/L EC50 Static

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Methyl ethyl ketone 78-93-3	0.29

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal of Wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl ethyl ketone 78-93-3	U159	Included in waste streams: F005, F039	200.0 mg/L regulatory level	U159

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Methyl ethyl ketone 78-93-3	Toxic Ignitable

14. TRANSPORT INFORMATION**Note**

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No	UN1193
Proper Shipping Name	Methyl Ethyl Ketone
Hazard Class	3
Packing Group	II
Reportable Quantity (RQ)	5000 lbs

IATA

UN/ID No	UN1193
Proper Shipping Name	Methyl Ethyl Ketone
Hazard Class	3
Packing Group	II

IMDG

UN/ID No	UN1193
Proper Shipping Name	Methyl Ethyl Ketone
Hazard Class	3
Packing Group	II

15. REGULATORY INFORMATION**International Inventories**

TSCA	Listed
------	--------

Legend:*TSCA - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List**EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances**ENCS - Japan Existing and New Chemical Substances**IECSC - China Inventory of Existing Chemical Substances**KECL - Korean Existing and Evaluated Chemical Substances**PICCS - Philippines Inventory of Chemicals and Chemical Substances*

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methyl ethyl ketone 78-93-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Not determined

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Methyl ethyl ketone 78-93-3	X	X	X

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	1	3	0	Not determined
HMIS	Health Hazards	Flammability	Physical Hazards	Personal Protection
	2	3	1	C

Issue Date: 01-Feb-2002
 Revision Date: 20-Nov-2023
 Revision Note: Container Change

Disclaimer

Information in the SDS is provided in good faith, but we assume no liability for its use or misuse. It is furnished without any warranty of merchantability or any other warranty, express or implied. We shall not be liable for any claims, losses or damages of any vendee or third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, however they arise. Users must make their own investigations to determine suitability.

End of Safety Data Sheet